



































Technology

#### **Product Brief**

- 100% All Solid Capacitor Design
- Supports Dual Channel DDR3 1600
- 1 x PCIe 3.0 x16 Slot, Supports AMD Quad CrossFireX™,  $CrossFireX^{\text{TM}}$
- PCIE Gigabit LAN
- Supports Intel® HD Graphics with Built-in Visuals
- Multi-VGA Output Options : D-Sub, DVI-D, HDMI
- Combo Cooler Option (C.C.O.)
- 7.1 CH HD Audio with Content Protection (Realtek ALC892 Audio Codec), Supports THX TruStudio™
- Supports ASRock XFast RAM, XFast LAN, XFast USB, OMG, Internet Flash, On/Off Play, UEFI System Browser
- Supports Intel Smart Connect, Intel Rapid Start, Intel Small Business Advantage
- Free Bundle: CyberLink MediaEspresso 6.5 Trial, ASRock MAGIX Multimedia Suite

| /ISRock              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                      | www.asrock.com                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Detail Specification |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Detail Spec          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Platform             | - ATX Form Factor: 12.0-in x 7.6-in, 30.5 cm x 19.3 cm<br>- All Solid Capacitor design                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| CPU                  | - Supports 3" and 2" Generation Intel" Core™ I7 / 15 / 13 in LGA1155 Package - 4 + 1 Power Phase Design - Supports Intel* Turbo Boost 2.0 Technology - Supports Intel* K-Series unlocked CPU - Supports Intel* Repid Technology - Supports Intel* Rapid Start Technology and Smart Connect Technology with Intel* Ivy Bridge CPU                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Chipset              | - Intel® B75<br>- Supports Intel® Small Business Advantage                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Memory               | Dual Channel DDR3 memory technology     4 x DDR3 DIMM slots     Supports DDR3 1600/1333/1066 non-ECC, un-buffered memory     (DDR3 1600 with Intel® by Bridge CPU, DDR3 1333 with Intel® Sandy Bridge CPU)     Max capacity of system memory: 32GB     - Supports Intel® Extreme Memory Profile (XMP) 1.3 / 1.2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Expansion Slot       | - 1 x PCI Express 3.0 x16 slot (PCIE1: x16 mode)  • PCIE 3.0 is only supported with Intel® V Bridge CPU. With Intel® Sandy Bridge CPU, it only supports PCIE 2.0.  • 1 x PCI Express 2.0 x16 slot (PCIE2: x4 mode)  • 1 x PCI Express 2.0 x1 slot  • 2 x PCI slots  • Supports AMD Quad CrossFireX™ and CrossFireX™                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Graphics             | * Intel® HD Graphics Built-in Visuals and the VGA outputs can be supported only with processors which are GPU integrated.  * Supports Intel® HD Graphics Built-in Visuals: Intel® Quick Sync Video 2.0, Intel® InTru™ 3D, Intel® Clear Video HD Technology, Intel® Insider™, Intel® HD Graphics 2500/4000  * Pixel Shader 5.0, Direct X1 with Intel® lay Bridge CPU. Pixel Shader 4.1, Direct X 10.1 with Intel® Sandy Bridge CPU.  * Max. Shared memory 1760MB  * Three VGA Output options: D-Sub, DVI-D and HDMI  * Supports BUMI 1.4a Technology with max. resolution up to 1920x1200 @ 60Hz  * Supports DVI with max. resolution up to 1920x1200 @ 60Hz  * Supports D-Sub with max. resolution up to 2048x1536 @ 75Hz  * Supports Sub with Can resolution up to 2048x1536 @ 75Hz  * Supports Auto Lip Sync. Deep Color (12bpc), xvYCC and HBR (High Bit Rate Audio) with HDMI (Compliant HDMI monitor is required)  * Supports HDCP function with DVI and HDMI ports  * Supports Full HD 1080p Blu-ray (BD) / HD-DVD playback with DVI and HDMI ports |
| Audio                | - 7.1 CH HD Audio with Content Protection (Realtek ALC892 Audio Codec) - Premium Blu-ray audio support - Supports THX TruStuction of Supports ThX                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| LAN                  | - PCIE x1 Gigabit LAN 10/100/1000 Mb/s - Realtlek RTL8111E - Supports Wake-On-LAN - Supports LAN Cable Detection - Supports Lan Cable Detection - Supports Energy Efficient Ethernet 802.3az - Supports PXE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Rear Panel I/O       | WO Panel - 1 x PSI/2 Keyboard Port - 1 x D-Sub Port - 1 x D-Sub Port - 1 x D-WI-D Port - 1 x HDMI Port - 1 x Cptical SPDIF Out Port - 1 x Cptical SPDIF Out Port - 4 x Ready-to-Use USB 2.0 Ports - 2 x Ready-to-Use USB 3.0 Ports - 1 x R.145 LAN Ports with LED (ACT/LINK LED and SPEED LED) - HD Audio Jack: Rear Speaker / Central / Bass / Line in / Front Speaker / Microphone                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| SATA3                | - 1 x SATA3 6.0 Gb/s connector by Intel® B75. supports NCQ, AHCI and Hot Plug functions - 2 x SATA3 6.0 Gb/s connectors by ASMedia ASM1061, support NCQ, AHCI and Hot Plug functions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| USB 3.0              | - 2 x Rear USB 3.0 ports, support USB 1.0/2.0/3.0 up to 5Gb/s - 1 x Front USB 3.0 header (supports 2 USB 3.0 ports), supports USB 1.0/2.0/3.0 up to 5Gb/s                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Connector            | - 5 x SATA2 3.0 Gb/s connectors, support NCQ, AHCl and Hot Plug functions - 3 x SATA3 6.0 Gb/s connectors                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                      | - 1 x IR header - 1 x CIR header - 1 x COM port header - 1 x COM y SpDir header - 1 x HOMI SpDir header                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

# Intel® Rapid Start

- 64Mb AMI UEFI Legal BIOS with GUI support
   Supports "Plug and Play"
   ACPI 1.1 Compliance Wake Up Events
   Supports jumperfree
   SMBIOS 2.3 1 Support
   CPU Core, IGPU, DRAM, 1.8V PLL, VTT, VCCSA Voltage Multi-adjustment **BIOS Feature**

USB 2.0 headers (support 4 USB 2.0 ports)
USB 3.0 header (supports 2 USB 3.0 ports)

- Drivers, Utilities, AntiVirus Software (Trial Version), CyberLink MediaEspresso 6.5 Trial, ASRock MAGIX Multimedia Suite OEM **Support CD**
- ASRock Extreme Turling Utility (AXTU)
  ASRock Instant Boot
  ASRock Instant Flash
  ASRock Instant Flash
  ASRock ASROCK Instant Flash
  ASRock ASROCK Instant Flash
  ASRock XFast USB
  ASRock XFast USB
  ASRock XFast LAN
  ASROCK XFast LAN
  ASROCK ONG (Online Management Guard)
  ASRock OMG (Online Management Guard)
  ASRock OMG (Office Management Guard)
   ASRock OMG (Office Plast Technology
   Hybrid Booster:
   ASRock OWG U-COP
   Boot Failure Guard (B.F.G.)
   Combo Cooler Option (C.C.O.)

**Unique Feature** 

**Hardware Monitor** 

Accessories

- CPU Temperature Sensing
  Chassis Temperature Sensing
  Chassis Temperature Sensing
  CPUI/Chassis/Power Fan Tachometer
  CPUI/Chassis Quiet Fan (Allow Chassis Fan Speed Auto-Adjust by CPU Temperature)
  CPUI/Chassis Fan Mulli-Speed Control
  Voltage Monitoring: +12V, +5V, +3.3V, CPU Vcore OS - Microsoft® Windows® 7 / 7 64-bit / Vista™ / Vista™ 64-bit / XP / XP 64-bit compliant Certifications FCC, CE, WHOL ErP/EuP ready power supply is required)

Quick Installation Guide, Support CD, I/O Shield 2 x SATA Data Cables (Optional)





### Intel® Small Business Advantage





Intel® SBA with Next Generation Intel® Core is a unique, out-of-the-box solution that delivers:

- · An easy-to-use interface
- · Relevant security and productivity applications
- Free and easy customization



# **Technology**

Intel Smart Connect Technology keeps content continuously updated while the PC is asleep! It will periodically wake up the PC while in a sleep state and check updates for things like email, Twitter, Facebook, etc



# Intel Smart Connect Intel Rapid Start **Technology**

Quickly return to where you left off with a PC that goes from deep-sleep to full awake in a flash.



#### ASRock OMG (Online Management Guard)

Fast, Easy and Free - ASRock OMG technology allows you to establish an internet curfew or restrict internet access at specified times. Administrators are able to schedule the starting and ending hours of internet access granted to other users.



#### Internet Flash

Internet Flash searches for available UEFI firmware updates from ASRock servers. System can auto-detect the latest UEFI from our servers and flash them within UEFI setup without entering Windows ® OS.





#### **Next-Gen PCIe 3.0**

- Higher bit rate 8.0GT/sHigher bandwidth per lane 1GB/s
- Higher efficiency 98.5% encoding efficiency
  100% backward compatible with
- previous PCI-E 2.0 / 1.0 standard

Note: Supported with 3rd Gen Intel Core Processor



# **Intel HD Graphics**

Intel® HD Graphics, simplifies your designs by eliminating additional discrete graphics hardware, while integrating stunning visuals and performance for immersive gaming.











# **THX TruStudio**

Delivering the fullest audio experience for games, music and movies.



# **UEFI System Browser**

UEFI system browser is a useful tool included in graphical UEFI. It can detect the devices and configurations that users are currently using in their PC.



# **On/Off Play**

Enjoy great audio experience from the portable audio devices via PC speaker even when the system is powered off.

# Cyberlink MediaEspresso 6.5 Trial

The fastest video media conversation software



## **MAGIX Multimedia Suite**

The ultimate solutions to enhance your media experience. From music management, music creation, video editing to photo management. Simply do more with your media than you ever thought possible.

