2A75M-DGS AMD A75 FCH (Hudson-D3)















AMD Radeon HD 7000 Series Graphics

AMD Dual Graphics

AMD Steady Video 2.0



AMP & XMP





A10 **A8** AG

Windows

Product Brief

- Support for Socket FM2 100W processors
- AMD A75 Hudson D3 Chipset Supports Native 6 x SATA3, 4 x USB 3.0 Ports
- Supports Dual Channel DDR3 2400+(OC)
- Supports Intel XMP 1.3/1.2 and AMD Memory Profile
- Supports AMD Dual Graphics
- Integrated AMD Radeon HD 7000 series graphics in A-series APU
- Dual-VGA Output : D-Sub, DVI-D
- 5.1 CH HD Audio (Realtek ALC662 Audio Codec)
- Supports ASRock XFast 555, OMG, Dehumidifier, Easy RAID Installer, Interactive UEFI, AMD Steady Video 2.0
- Free Bundle : CyberLink MediaEspresso 6.5 Trial, ASRock MAGIX Multimedia Suite

Detail Specification - Micro ATX Form Factor: 8.9-in x 7.6-in, 22.6 cm x 19.3 cm - Solid Capacitor for CPU power Platform Support for Socket FM2 100W processors Supports AMD's Cool 'n' Quiet Technology UMI-Link GEN2 CPU Chipset - AMD A75 FCH (Hudson-D3) Dual Channel DDR3 memory technology 2 x DDR3 DIMM slots Memory 2 x DUros Dimini sids Supports DDR3 2400+(OC)/2133(OC)/1866/1600/1333/1066/800 non-ECC, un-buffered men Max, capacity of system memory: 32GB Supports Intel[®] Extreme Memory Profile (XIP) 1.3 / 1.2 Supports AMD Memory Profile (AMP) Expansion Slot -1 x PCI Express 2.0 x16 slot (PCIE1 @ x16 mode) -1 x PCI Express 2.0 x16 slot -1 x PCI slot - Supports AMD Dual Graphics Integrated AMD Radeon HD 7000 series graphics in A-series APU DirectX 11, Pixel Shader 5.0 Max. shared memory 2GB Dual VGA Output: support DVI and D-Sub ports by independent display controllers Supports Dual-link DVI with max. resolution up to 2560x1600 @ 75Hz Supports D-bub with max. resolution up to 1920x1600 @ 60Hz Supports AMD Steady Video[™] 2.0: New video post processing capability for automatic jutter reduction on home/online video Graphics reduction on home/online video Supports HDCP function with DVI port Supports Full HD 1080p Blu-ray (BD) / HD-DVD playback with DVI port

Audio	- 5.1 CH HD Audio (Realtek ALC662 Audio Codec)
LAN	- PCIE x1 Gigabit LAN 10/100/1000 Mb/s - Realtek RTL8111E - Supports Wake-On-LAN - Supports LAN Cable Detection - Supports Lenergy Efficient Ethernet 802.3az - Supports PXE
Rear Panel I/O	I/O Panel - 1 x PS/2 Mouse/Keyboard Port - 1 x D-Sub Port - 1 x D-Sub Port - 1 x DVI-D Port - 4 x Ready-to-Use USB 2.0 Ports - 2 x Ready-to-Use USB 3.0 Ports - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED) - HD Audio Jack: Line in / Front Speaker / Microphone
SATA3	 - 6 x SATA3 6.0 Gb/s connectors, support RAID (RAID 0, RAID 1 and RAID 10), NCQ, AHCI and "Hot Plug" functions
USB 3.0	- 2 x Rear USB 3.0 ports, support USB 1.1/2.0/3.0 up to 5Gb/s - 1 x Front USB 3.0 header (supports 2 USB 3.0 ports), supports USB 1.1/2.0/3.0 up to 5Gb/s
Connector	- 6 x SATA3 6.0 Gb/s connectors - 1 x IR header - 1 x CIR header - 1 x CIR header - 1 x COM port header - 1 x COU Fan connector (4-pin) - 1 x CDU Fan connector (4-pin) - 1 x Chassis Fan connector (3-pin) - 24 pin ATX power connector - 4 pin ATX power connector - 4 pin ATX power connector - Front panel audio connector - 3 x USB 2.0 headers (support 6 USB 2.0 ports) - 1 x USB 3.0 header (support 2 USB 3.0 ports)
BIOS Feature	- 64Mb AMI UEFI Legal BIOS with GUI support - Supports "Plug and Play" - ACPI 1.1 Compliance Wake Up Events - Supports jumperfree - SMBIOS 2.3.1 Support - DRAM, VDDP, VDDR, SB Voltage Multi-adjustment
Support CD	- Drivers, Utilities, AntiVirus Software (Trial Version), AMD Live! Explorer, CyberLink MediaEspresso 6.5 Trial, ASRock MAGIX Multimedia Suite - OEM
Unique Feature	ASRock Extreme Tuning Utility (AXTU) ASRock Instant Boot ASRock Instant Flash ASRock ASRath Flash ASRock XFast LAN ASRock XFast LAN ASRock XFast LAN ASRock XFast RAM ASRock Crashless BIOS ASRock KTEl System Browser ASRock Interret Flash ASRock LOCP
Hardware Monitor	- CPU Temperature Sensing - Chassis Temperature Sensing - CPU/Chassis/Power Fan Tachometer - CPU/Chassis Quiet Fan - CPU/Chassis Fan Multi-Speed Control - Voltage Monitoring: +12V, +5V, +3.3V, Vcore
OS	- Microsoft® Windows® 7 / 7 64-bit / Vista™ / Vista™ 64-bit / XP compliant
Certifications	- FCC, CE, WHQL - ErP/EuP Ready (ErP/EuP ready power supply is required)
Accessories	- Quick Installation Guide, Support CD, I/O Shield - 2 x SATA data cables

The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

FM2A75M-DGS

AMD A75 FCH (Hudson-D3)





AMD Radeon HD 7000 Series Graphics

Engineered for supremacy, designed for efficiency and packed with incredible features, the AMD Radeon HD 7000 Series offers the world's most advanced graphics.

DirectX[®] 11

1213.0 MHz

Dual Channel D

DirectX® 11 is the very latest in high-speed, high-fidelity gaming and computing. It can enable not just more visually stunning games, but significant performance improvements in some of your favorite websites and everyday applications.

AMD Dual Graphics AMD Steady Video 2.0 The AMD Dual Graphics

technology combines APU and GPU computing power to optimize user's visual experience.

DUAL

GRAPHICS

TECHNOLOGY

Bringing the best video experience! Compared to v1.0, AMD Steady Video 2.0 provides more tech advances such as Letter/Pillar Boxed Content, Indicator Overlay, Enhanced Algorithm Effectiveness, etc.



AMP & XMP

Not only supporting AMD Memory Profile (AMP), ASRock FM2 Motherboard Series also come with Intel XMP memory tuning kits, making it's easy to get maximum memory performance from your system.



Interactive UEFI

DirectX'11

ASRock Interactive UEFI is a blend of system configuration tools, cool sound effects and stunning visuals. The unprecedented UEFI provides a more attractive interface and brings a lot more amusing.



ASRock Dehumidifier

Users may prevent motherboard damages due to dampness by enabling "Dehumidifier Function". When enabling Dehumidifier Function, the computer will power on automatically to dehumidify the system after entering S4/S5 state



ASRock OMG (Online Management Guard)

Fast, Easy and Free – ASRock OMG technology allows you to establish an internet curfew or restrict internet access at specified times. Administrators are able to schedule the starting and ending hours of internet access granted to other users.



The specification is subject to change without notice. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

FM2A75M-DGS AMD A75 FCH (Hudson-D3)



Internet Flash

Internet Flash searches for available UEFI firmware updates from ASRock servers. System can auto-detect the latest UEFI from our servers and flash them within UEFI setup without entering Windows * OS.

Easy RAID Installer Cyberlink

Easy RAID Installer can help you install the RAID driver easily without floppy drive. It can copy the RAID driver from a support CD to your USB storage device with just one simple click in UEFI setup.

Cyberlink MediaEspresso 6.5 Trial

CyberLink MediaEspresso 6.5 trial supports hardware transcoding and is optimized to accelerate conversion of all your favorite media files for your favorite portable players.



MAGIX Multimedia Suite

The ultimate solutions to enhance your media experience. From music management, music creation, video editing to photo management. Simply do more with your media than you ever thought possible.





