Z77 Performance

Intel® Z77 Chipset










































Intel® Smart Connect Intel® Rapid Start Technology

Technology

Product Brief

- ASRock DuraCaps
- Digi Power Design, 8 + 4 Power Phase Design
- Supports Dual Channel DDR3 2800+(OC)
- 1 x PCIe 3.0 x16 Slot, Supports AMD Quad CrossFireX™, $CrossFireX^{\text{TM}}$
- Supports Broadcom Gigabit LAN
- Supports Intel® HD Graphics with Built-in Visuals
- Multi-VGA Output Options : D-Sub, DVI-D, HDMI
- Combo Cooler Option (C.C.O.)
- 7.1 CH HD Audio with Content Protection (Realtek ALC892 Audio Codec), Supports THX TruStudio™
- Supports ASRock XFast RAM, XFast LAN, XFast USB, On/Off Play, UEFI System Browser
- Supports Fatal1ty F-Stream, Fatal1ty Mouse Port
- Supports Intel Smart Connect, Intel Rapid Start, Lucid Virtu Universal MVP
- Free Bundle: CyberLink MediaEspresso 6.5 Trial, ASRock MAGIX Multimedia Suite

Audio	- Premium Blu-ray audio support - Supports THX TruStudio™
LAN	- PCIE x1 Gigabit LAN 10/100/1000 Mb/s - Broadcom BCM57/B1 - Supports Wake-On-LAN - Supports Energy Efficient Ethernet 802.3az - Supports PXE
Rear Panel I/O	I/O Panel - 1 x PSIZ Keyboard Port - 1 x PSIZ Keyboard Port - 1 x D.V.D Port - 1 x D.V.D Port - 1 x HDMI Port - 1 x HDMI Port - 1 x HDMI Port - 3 x Ready-to-Use USB 2.0 Ports - 3 x Ready-to-Use USB 2.0 Ports - 1 x Falatily Mouse Port (USB 2.0) - 1 x eSATA2 Connector - 4 x Ready-to-Use USB 3.0 Ports - 1 x R.J.45 LAN Port with LED (ACT/LINK LED and SPEED LED) - 1 x Clear CMOS Switch with LED - 1 x Clear CMOS Switch with LED - HD Audio Jack: Rear Speaker / Central / Bass / Line in / Front Speaker / Microphone
SATA3	- 2 x SATA3 6.0 Gb/s connectors, support RAID (RAID 0, RAID 1, RAID 5, RAID 10, Intel Rapid Storage and Intel Smart Response Technology), NCQ, AHCI and "Hot Plug" functions
USB 3.0	- 2 x Rear USB 3.0 ports by Intel® Z77, support USB 1.0/2.0/3.0 up to 5Gb/s - 2 x Rear USB 3.0 ports by Etron EJ168A, support USB 1.0/2.0/3.0 up to 5Gb/s - 1 x Front USB 3.0 header by Intel® Z77 (supports 2 USB 3.0 ports), supports USB 1.0/2.0/3.0 up to 5Gb/s
Connector	 - 4 x SATA2 3.0 Gb/s connectors, support RAID (RAID 0, RAID 1, RAID 5, RAID 10, Intel Rapid Storage and Intel Smart Response Technology), NCO, AHCI and Hot Plug functions (SATA2_3 connector is shared with eSATA2 port) - 2 x SATA3 6.0 Gb/s connectors 1 x R Nader

compilant HDMI monitor is required) upports HDCP function with DVI and HDMI ports upports Full HD 1080p Blu-ray (BD) / HD-DVD playback with DVI and HDMI ports

- 7.1 CH HD Audio with Content Protection (Realtek ALC892 Audio Codec)

1 X IR header
1 COMport header
1 X HDM_SPDIF header
1 X HDM_SPDIF header
1 X HDML SPDIF header
1 X HDML SPDIF header
1 X HDML SPDIF header
2 PLIC/hassis/Power FAN connector
8 pin 12V power connector
8 pin 12V power connector
3 X USB 2.0 headers (support 6 USB 2.0 ports)
1 X USB 3.0 header (supports 2 USB 3.0 ports)
1 X USB 3.0 header (supports 2 USB 3.0 ports)

1 x Power Switch with LED 1 x Reset Switch with LED 1 x Clear CMOS Switch with LED **Smart Switch**

64Mb AMI UEFI Legal BIOS with GUI support Supports "Plug and Play" ACPI 1.1 Compliance Wake Up Events Supports jumperfree SMBIOS 2.3 T Support CPU Core, IGPU, DRAM, 1.8V PLL, VTT, VCCSA Voltage Multi-adjustment **BIOS Feature**

Support CD

Unique Feature

F. Stream

- ASRock Instant Boot
- ASRock Instant Boot
- ASRock Instant Flash
- ASRock SmartView
- ASRock SmartView
- ASRock AFRST LAN
- ASRock On/Off Play Technology
- Lucid Virtu Universal MVP
- ASRock On/Off Play Technology
- Hybrid Boosteriery Stepless Control
- ASRock Childre Guard (B. F.G.)
- Boot Failure Guard (B. F.G.)
- Combo Cooler Option (C.C.O.)
- Good Night LED

CPU Temperature Sensing
Chassis Temperature Sensing
Chassis Temperature Sensing
CPUI/Chassis/Power Fan Tachometer
CPUI/Chassis Quiet Fan (Allow Chassis Fan Speed Auto-Adjust by CPU Temperature)
CPUI/Chassis Fan Mulli-Speed Control
Voltage Monitoring: +12V, +5V, +3.3V, CPU Vcore **Hardware Monitor**

Microsoft® Windows® 7 / 7 64-bit / Vista™ / Vista™ 64-bit / XP / XP 64-bit compliant

Certifications FCC, CE, WHQL ErP/EuP Ready (ErP/EuP ready power supply is required) Quick Installation Guide, Support CD, I/O Shield 2 x SATA Data Cables (Optional) **Accessories**











5X Faster for Photoshop Execution

XFast RAM will create a virtual disk from the system memory to boost the performance for Photoshop. It can even perform 5X faster than before.



The performance boost percentage may vary with a different configuration.



Virtu Universal MVP - Uncompromised Game Response Performance



1. HyperFormance™:

A new technology which combines integrated and discrete graphics for uncompromised performance and get up to a 90% performance boost!

Virtu HyperFormance ON (discrete VGA+ integrated VGA)

■ Virtu HyperFormance OFF (discrete VGA only)

3DMark11 (Extreme 1080p) - Graphics Score

2. Virtual Vsync:

A technology designed to solve the ever lasting debate between quality and performance. Bring GPU performance from 60 FPS Vsync limit back to its maximum while keeping Vsync image quality and no tearing.



3. Switchable Graphics:

Dynamically assigns tasks to the best graphics resource regardless of physical cable connections.







Intel Smart Connect Intel Rapid Start Technology

Intel Smart Connect Technology keeps content continuously updated while the PC is asleep! It will periodically wake up the PC while in a sleep state and check updates for things like email. Twitter, Facebook, etc.




Technology

Quickly return to where you left off

with a PC that goes from deep-sleep to full awake in a flash.

ASRock DuraCaps

All the capacitors on this board are built with 100% all solid capacitors. With these solid caps, ASRock motherboard is allowed to perform more stably and ensure longer lifetime.



Digi Power





Z77 Performance

Intel® Z77 Chipset



8 + 4 Power Phase Design

To improve CPU power solution, this board is designed with the advanced 8 + 4 power phase design which signatures tough components and smooth power delivery to the CPU.

4 x DDR3 2800+ (OC)

Fatal1ty 7-Series motherboards unlock maximum memory performance, coming with 4 DIMM slots for dual-channel memory, supporting up to DDR3 2800+(OC) MHz!

F-Stream

The Fatal1ty F-Stream tuning program is an all-in-1 software utility that supports overclocking and hardware tuning such as energy usage, H/W monitor, fan speed control , Fatal1ty Mouse Port Configuration and XFast RAM.

F-STREAM TUNING

Fatal1ty Mouse Port

Fatal1ty Mouse Port is a customizable technology for PC gamers and part of F-Stream. After plugging a USB mouse into the Fatal1ty Mouse Port and running F-Stream, gamers can use Fatal1ty's personally preferred mouse polling rate at 500 Hz. F-Stream also provides flexibility for gamers to adjust the mouse polling rate from 125 Hz to 1000 Hz, which helps professional gamers experience smoother gameplay and a faster mouse response





Next-Gen PCIe 3.0

Higher bandwidth per lane - 1GB/sHigher efficiency - 98.5% encoding efficiency

· Higher bit rate - 8.0GT/s

· 100% backward compatible with

previous PCI-E 2.0 / 1.0 standard

Note: Supported with 3rd Gen Intel Core Processor



Intel HD Graphics

Intel® HD Graphics, simplifies your designs by eliminating additional discrete graphics hardware, while integrating stunning visuals and performance for immersive gaming.

On/Off Play

Enjoy great audio experience from the portable audio devices via PC speaker even when the system is powered off.

THX TruStudio™

THX TruStudio is specially designed to bring the same great audio experience found in live performances, films, and recording studios to the PC.



















UEFI System Browser

The UEFI system browser can let you easily check your current system configuration in UEFI setup.

