## Z77 Professional-M

Intel® Z77 Chipset





































Technology Technology

#### Product Brief

- Premium Gold Caps
- Digi Power Design
- Supports Dual Channel DDR3 2800+(OC)
- 2 x PCle 3.0 x16 Slots, Supports AMD Quad CrossFireX™, 3-Way CrossFireX, CrossFireX™ and NVIDIA Quad SLI™,  $SLI^{TM}$
- PCIE Gigabit LAN
- Supports Intel® HD Graphics with Built-in Visuals
- Multi-VGA Output Options : DVI-D, D-Sub, HDMI
- Combo Cooler Option (C.C.O.)
- 7.1 CH HD Audio with Content Protection (Realtek ALC898 Audio Codec), Supports THX TruStudio™
- Supports ASRock XFast RAM, XFast LAN, XFast USB, **UEFI System Browser**
- Supports Intel Smart Connect, Intel Rapid Start, Lucid Virtu Universal MVP
- Free Bundle: CyberLink MediaEspresso 6.5 Trial, ASRock MAGIX Multimedia Suite

F	ATAL TY www.asrock.com
Detail Specification	
Platform	- Micro ATX Form Factor: 9.6-in x 9.6-in, 24.4 cm x 24.4 cm - Premium Gold Capacitor design (100% Japan-made high-quality Conductive Polymer Capacitors)
CPU	Supports 3 <sup>st</sup> and 2 <sup>st</sup> Generation Intel® Core™ 17 / 15 / 13 in LGA1155 Package  - B + 3 Power Design  - 8 + 3 Power Phase Design  - Supports Intel® Turbo Boost 2.0 Technology  - Supports Intel® K-Series unlocked CPU  - Supports Hyper-Threading Technology  - Supports Hyper-Threading Technology and Smart Connect Technology with Intel® Ivy Bridge CPU
Chipset	- Intel® Z77
Memory	- Dual Channel DDR3 memory technology - 4 x DDR3 DIMM slots - Supports DDR3 2800+(CC)/2400(CC)/2133(CC)/1866(CC)/1600/1333/1066 non-ECC, un-buffered memory - Max. capacity of system memory: 32GB - Supports intel <sup>®</sup> Extreme Memory Profile (XMP) 1.3 / 1.2
Expansion Slot	- 2 x PCI Express 3.0 x16 slots (PCIE1/PCIE3: single at x16 (PCIE1) / x8 (PCIE3) or dual at x8/x8 mode)  *PCIE 3.0 is only supported with Intel* by Bridge CPU. With Intel* Sandy Bridge CPU, it only supports PCIE 2.0.  -1 x PCI Express 2.0 x16 slot (PCIE4: x4 mode)  -1 x PCI Express 2.0 x1 slot -2 supports AMD Quad CrossFireX™, 3-Way CrossFireX™ and CrossFireX™  - Supports NVIDIA* Quad SLI™ and SLI™

rapnics	which are GPU integrated.
	- Supports Intel® HD Graphics Built-in Visuals : Intel® Quick Sync Video 2.0, Intel® InTru™ 3D, Intel®
	Clear Video HD Technology, Intel® Insider™, Intel® HD Graphics 2500/4000.
	- Pixel Shader 5.0, DirectX 11 with Intel® Ivy Bridge CPU. Pixel Shader 4.1, DirectX 10.1 with
	Intel® Sandy Bridge CPU.
	- Max. shared memory 1760MB
	- Four VGA Output options: D-Sub, DVI-D, HDMI and DisplayPort
	- Supports HDMI 1.4a Technology with max. resolution up to 1920x1200 @ 60Hz
	- Supports DVI with max. resolution up to 1920x1200 @ 60Hz

Supports D-Sub with max. resolution up to 2048x1536 @ 75Hz
Supports DisplayPort with max. resolution up to 2566x1600 @ 60Hz
Supports Auto Lip Sync, Deep Color (12bpc), xvYCC and HBR (High Bit Rate Audio) with HDMI
(Compliant HDMI monitor is required)
Supports HDCP function with DVI, HDMI and DisplayPort ports
Supports Full HD 1060p Bit-ray (BD) / HD-DVD playback with DVI, HDMI and DisplayPort ports

Audio LAN

PCIE x1 Gigabit LAN 10/100/1000 Mb/s Broadcom BCM57781 Supports Wake-On-LAN Supports Energy Efficient Ethernet 802.3az Supports PXE

Rear Panel I/O

I/O Panel
- 1.1 P.S/Z Keyboard/Mouse Port
- 1.2 D.S/D Port
- 1.3 D.S/D Port
- 1.3 D.S/D Port
- 1.4 D.S/D Port
- 1.4 D.S/D Port
- 1.4 D.S/D Port
- 1.5 D.S/D Port
- 1.5 D.S/D Port
- 1.6 D.S/D Port
- 1.6 D.S/D Port
- 1.7 Ready-to-Use USB 2.0 Port
- 1.8 Ready-to-Use USB 2.0 Port
- 1.8 REATA3 Connector
- 4.8 Ready-to-Use USB 3.0 Ports
- 1.1 R.J-45 L.AN Port with LED (ACT/LINK LED and SPEED LED)
- 1.1 K.Glac T.GMOS Switch with LED
- 1.1 K.GMOS Switch with LED
- 1.1 K.GM

2 x SATA3 6.0 Gb/s connectors by Intel® 277, support RAID (RAID 0, RAID 1, RAID 5, RAID 10, Intel Rapid Storage and Intel Smart Response Technology), NCO, AHCI and "Hot Plug" functions 2 x SATA3 6.0 Gb/s connectors by ASMedia ASM1061, support NCO, AHCI and "Hot Plug" functions (SATA3\_A2 connector is shared with eSATA3 port) SATA3

2 x Rear USB 3.0 ports by Intel\* 277, support USB 1.0/2.0/3.0 up to 5Gb/s 2 x Rear USB 3.0 ports by ASMedia ASM1042, support USB 1.0/2.0/3.0 up to 5Gb/s 1 x Front USB 3.0 header by Intel\* 277 (supports 2 USB 3.0 ports), supports USB 1.0/2.0/3.0 up to 5Gb/s **USB 3.0** 

up to 5Gb/s

4 x SATA2 3.0 Gb/s connectors, support RAID (RAID 0, RAID 1, RAID 5, RAID 10, Intel Rapid Storage and Intel Smart Response Technology), NCQ, AHCI and Hot Plug functions

4 x SATA3 6.0 Gb/s connectors

1 x IR header

1 x CIR header (support 6 USB 2.0 ports)

1 x USB 3.0 headers (support 5 USB 3.0 ports)

1 x USB 3.0 header (supports 2 USB 3.0 ports)

1 x USR 3.0 header (supports 2 USB 3.0 ports) Connector

**BIOS Feature** 

**Smart Switch** 

64Mb AMI UEFI Legal BIOS with GUI support
Supports 'Plug and Play'
ACPI 1.1 Compliance Wake Up Events
Supports jumperfree
SMBIOS 2.3 I Support
CPU Core, IGPU, DRAM, 1.8V PLL, VTT, VCCSA Voltage Multi-adjustment

Drivers, Utilities, AntiVirus Software (Trial Version), CyberLink MediaEspresso 6.5 Trial, ASRock MAGIX Multimedia Suite - OEM Support CD **Unique Feature** 

ASRock XFast RAM
ASRock Crashless BIOS
Lucid Virtu Universal MVP
- Lucid Virtu Vir

Good Night LEU
CPU Temperature Sensing
Chassis Temperature Sensing
Chassis Temperature Sensing
CPUI/ChassiSPower Fan Tachometer
CPUI/Chassis Quiet Fan (Allow Chassis Fan Speed Auto-Adjust by CPU Temperature)
CPUI/Chassis Fan Multi-Speed Control
Voltage Monitoring: +12V, +5V, +3.3V, CPU Vcore **Hardware Monitor** 

Microsoft® Windows® 7 / 7 64-bit / Vista™ / Vista™ 64-bit / XP / XP 64-bit compliant Certifications FCC, CE, WHQL ErP/EuP Ready (ErP/EuP ready power supply is required)

1 x ASRock SLI\_Bridge Card Quick Installation Guide, Support CD, I/O Shield 4 x SATA Data Cables (Optional) 1 x SATA 1 to 1 Power Cable (Optional) **Accessories** 











5X Faster for Photoshop Execution

XFast RAM will create a virtual disk from the system memory to boost the performance for Photoshop. It can even perform 5X faster than before.



latency in the game after setting online game priority higher.

The performance boost percentage may vary with a different configuration.



## Virtu Universal MVP - Uncompromised Game Response Performance



#### 1. HyperFormance™:

A new technology which combines integrated and discrete graphics for uncompromised performance and get up to a 90% performance boost!

Virtu HyperFormance ON (discrete VGA+ integrated VGA)

■ Virtu HyperFormance OFF (discrete VGA only)

3DMark11 (Extreme 1080p) - Graphics Score

#### 2. Virtual Vsync:

A technology designed to solve the ever lasting debate between quality and performance. Bring GPU performance from 60 FPS Vsync limit back to its maximum while keeping Vsync image quality and no tearing.



#### 3. Switchable Graphics:

Dynamically assigns tasks to the best graphics resource regardless of physical cable connections.







# Technology

Intel Smart Connect Technology keeps content continuously updated while the PC is asleep! It will periodically wake up the PC while in a sleep state and check updates for things like email. Twitter, Facebook, etc.



## Intel Smart Connect Intel Rapid Start Technology

Quickly return to where you left off with a PC that goes from deep-sleep to full awake in a flash.



## Premium Gold Caps

Premium Gold Caps are 100% made in Japan; these solid capacitors are sleek, high gloss caps with a premium gold coating representing long life and stable performance.



#### Digi Power

By adopting digital Pulse-width modulation (PWM), the Z77 motherboard can provide CPU Vcore voltage more efficiently and smoothly.



# Z77 Professional-M

Intel® Z77 Chipset



### 8 + 3 Power Phase Design

To improve CPU power solution, this board is designed with the advanced 8 + 3 power phase design which signatures tough components and smooth power delivery to the CPU.

## 4 x DDR3 2800+(OC) Fatal1ty Mouse Port Next-Gen PCIe 3.0

Fatal1ty 7-Series motherboards unlock maximum memory performance, coming with 4 DIMM slots for dual-channel memory, supporting up to DDR3 2800+(OC) MHz!



Fatal1ty Mouse Port is a customizable technology for PC gamers and part of F-Stream. After plugging a USB mouse into the Fatal1ty Mouse Port and running F-Stream, gamers can use Fatal1ty's personally preferred mouse polling rate at 500 Hz. F-Stream also provides flexibility for gamers to adjust the mouse polling rate from 125 Hz to 1000 Hz, which helps professional gamers experience smoother gameplay and a faster mouse response



- · Higher bit rate 8.0GT/s
- Higher bandwidth per lane 1GB/s
- Higher efficiency 98.5% encoding efficiency
   100% backward compatible with previous PCI-E 2.0 / 1.0 standard

Note: Supported with 3rd Gen Intel Core Processor



### Intel HD Graphics

Intel® HD Graphics, simplifies your designs by eliminating additional discrete graphics hardware, while integrating stunning visuals and performance for immersive gaming.

## THX TruStudio™

THX TruStudio is specially designed to bring the same great audio experience found in live performances, films, and recording studios to the PC.

### **UEFI System** Browser

The UEFI system browser can let you easily check your current system configuration in UEFI setup.

#### F-Stream

The Fatal1ty F-Stream tuning program is an all-in-1 software utility that supports overclocking and hardware tuning such as energy usage, H/W monitor, fan speed control , Fatal1ty Mouse Port Configuration and XFast RAM.













